

# BREECHINGS/WYE



## UNCONTROLLED BREECHINGS/WYE

### MODELS:

**053700**

Dividing, single male instantaneous inlet, two female instantaneous outlets, or screw thread to customer requirements

**053900**

Collecting, single female instantaneous inlet, two male instantaneous outlets, or screw thread to customer requirements

### MATERIALS:

Breeching body and adapters available in heat treated cast aluminium, or LG2 gunmetal. Light alloy polished, gunmetal in red painted finish

**APPROX WEIGHT:** Light Alloy 3 kg, Gunmetal 9 kg



## CONTROLLED BREECHINGS/WYE

Possibly the most durable controlled breaching manufactured. Stainless steel shafts or spindles for strength and corrosion resistance, 'O' ring seals for maintenance free sealing, computer controlled machining ensures accurate dimensions and high quality finish. Closure by means of a positive lift valve to avoid jamming. Hydraulically efficient waterway. Revolving handwheels for fast action, and ensure no water hammer.

### MODELS:

**053800**

Single male 70 mm instantaneous inlet, twin female 70 mm instantaneous

**110100**

Single male British instantaneous inlet, twin British instantaneous outlets

### OPTIONS:

Storz or screw threads to customer requirements

### MATERIALS:

Breeching body and adapters available in heat treated cast aluminium, or LG2 gunmetal. Adaptors polished, breeching body in red painted finish

**APPROX WEIGHT:** Light Alloy 3 kg, Gunmetal 9 kg



**If you do not see what you want in our brochures, please call us! We cannot show every item**

*Due to continued improvement the right is reserved to modify specifications without prior notice*



PSL

PO Box 69-028, 10 Akatea Road, Glendene, Auckland 0645, New Zealand  
Ph: +64 9 8188048 Fax: +64 9 818 4484 Email: sales@firemaster.co.nz  
Web: [www.firemaster.co.nz](http://www.firemaster.co.nz)

**"Fire & Safety Solutions"**