

FIREMASTER INDUSTRIAL FIRE HOSE



FEATURES:

- * Lightweight and highly flexible
- * Small coil diameter
- * resistance to weathering and ozone
- * Mildew and rotproof
- * Easy to repair



Available with either Instantaneous, Storz or Camlock couplings.

APPLICATIONS:

- * Industrial and rural fire brigades
- * Military
- * Static building protection
- * Commercial and civil engineering

CONSTRUCTION:

JACKET: High tenacity polyester yarn, circular woven in twill weave.
2-ply warp threads, lightweight, nevertheless high bursting pressure

LINING: High grade synthetic rubber, steam vulcanized
Very smooth for friction loss.

INTERNAL (MM)	DIMENSION (INCH)	WEIGHT per m (GRAM)	WORKING PRESSURE (MPa/PSI)	TESTING PRESSURE (MPa/PSI)	BURSTING PRESSURE (MPa/PSI)
38	1 1/2"	205	1,6/230	2,5/365	5,0/725
45	1 3/4"	235	1,6/230	2,5/365	5,0/725
50	2"	260	1,6/230	2,5/365	5,0/725
64	2 1/2"	360	1,6/230	2,5/365	5,0/725
70	2 3/4"	385	1,6/230	2,5/365	5,0/725
75	3"	410	1,6/230	2,5/365	5,0/725
100	4"	610	1,2/175	1,8/260	3,6/525
150	6"	950	1,0/145	1,5/220	3,0/435

If you do not see what you want in our brochures, please call us! We cannot show every item
Due to continued improvement the right is reserved to modify specifications without prior notice



PSL
PO Box 69-028, 10 Akatea Road, Glendene, Auckland 0645, New Zealand
Ph: +64 9 8188048 Fax: +64 9 818 4484 Email: sales@firemaster.co.nz
Web: www.firemaster.co.nz

"Fire & Safety Solutions"