

**PHOTOELECTRIC SMOKE ALARM**

**With "HUSH" feature - Model SS-166S**



Photoelectric technology is more sensitive to detecting slow smouldering fires which may smoulder for hours before bursting into flames.  
The SS-166S do not contain radioactive material and is harmless to the environment.

**FEATURES:**

- DIY unit, easy and simple installation
- High sensitivity & reliability
- Low battery signal
- Alarm/Power indicator
- Test button
- Hush Feature
- Loud 85dB alarm signal
- Photoelectric chamber: for slow smoldering fires
- Battery life minimum 1 year
- Supplied with fixing kit



Ref. 7405

**SPECIFICATIONS:**

Power Source:	9Vdc Alkaline or Carbon Zinc battery GOLD PEAK GP1604P, Golden Power 16040, EVEREADY PP3S, DURACELL MN16049V
Operating Current:	10 uA (normal) and <20 mA (alarm working)
Sensitivity to Smoke:	Comply to BSI or VDS standard
Operating Temperature:	0°C - 40°C
Ambient Humidity:	10% - 90%
Plastic Material:	ABS
Overall Dimensions:	45 mm (H) x 106 mm (D)
Colour:	Bright White
Alarm Sound Level:	85 Decibels at 3 meters minimum
Battery Life:	One year minimum
Warranty:	5 Year warranty (excludes batteries)
Approvals:	Kitemarked to BS5446 Pt1 2000, VDS, UL, CE

***If you do not see what you want in our brochures, please call us! We cannot show every item***  
*Due to continued improvement the right is reserved to modify specifications without prior notice*



PSL

PO Box 69-028, 10 Akatea Road, Glendene, Auckland 0645, New Zealand  
Ph: +64 9 8188048 Fax: +64 9 818 4484 Email: sales@firemaster.co.nz  
Web: [www.firemaster.co.nz](http://www.firemaster.co.nz)

**"Fire & Safety Solutions"**