



Forestry Couplings

Precision machined PSL forestry couplings are made from heat treated aluminium alloy.

Supplied complete with soft annealed copper ferrules and neoprene washer, to Forestry Specifications ND13, ND20, ND14 and ND15. Special stainless steel ball race, maintenance free, built into the female half.



- Part No. 025200 25mm coupling set
- Part No. 025300 Spare 25mm copper ferrules
- Part No. 028300 41mm coupling set
- Part No. 025400 Spare 41mm copper ferrules
- Part No. P4521 Forestry coupling rubber washer, standard in both sizes



Forestry Nozzles

- Part No. 7658 UFS 1575 41 MM Forestry Nozzle, tough red polycarbonate body. Flow rate 120 lpm Jet or 110 lpm Spray at 700 kPa.
- Part No. 7659 UFS 1030 25 mm Forestry Nozzle, tough red polycarbonate body. Flow rate 50 lpm Jet or 55 lpm Spray at 700 kPa.

Nozzles have U.L. Approvals



Part No. 026000 LA 41 mm Blank Cap, Male, Forestry Part No ND91

Part No. 026500 LA 41 mm Double Female Connector, Forestry Part No ND265

Part No. 026100 LA 41 mm Blank Cap, Female, Forestry Part No ND49 (not illustrated)

Part No. 026400 LA 41 mm Thread Protector, Female to Male BSP, Knurled,

If you do not see what you want in our brochures, please call us! We cannot show every item
Due to continued improvement the right is reserved to modify specifications without prior notice



PSL

PO Box 69-028, 10 Akatea Road, Glendene, Auckland 0645, New Zealand
Ph: +64 9 8188048 Fax: +64 9 818 4484 Email: sales@firemaster.co.nz
Web: www.firemaster.co.nz

Rev: 1

"Fire & Safety Solutions"