



**FORESTRY HYDROBLENDER
(PART NO 028000)**

Used to improve the wetting action of water for rural firefighting. A pair of special soap capsules is inserted in the Hydroblender, water enters from one side, spirals up around the capsule, gradually dissolving it, and leaves from the opposite side. The treated water saturates dry vegetation more effectively. An excellent tool also for deep-seated fires in hay, baled material or paper. Specially designed 100 mm round thread cap for fast removal, yet safe operation. Also supplied with mounting brackets for vehicle applications Part No 027900, or with optional backpack carry frame. Carry frame Part No 7601, available with two spare capsule holders if requested.



FORESTRY BALL VALVE CONTROLLED DIVIDING BREECHING

Marine anodised balls for extended life. Gives easy, positive flow control on each outlet. Light weight, with stainless spindle for strength. Heat-treated light alloy body and handles. Durable seals cope well with even aggressive pumice type water. Inlet 38mm male BSP, 2 x outlets 38mm" male BSP (Part No 027500)



OPTIONS:

Part No 024000 - Fitted with double female ball race inlet, and thread protectors on outlets

Part No 027600 - Fitted with an instantaneous inlet and male BSP outlets.

INSTANTANEOUS TO FORESTRY UNCONTROLLED BREECHING

For the connection of two forestry fire hose lines to a large pump outlet. In heat-treated light alloy. Threads, 38mm male BSP, or to client specs. Supplied with two blank caps secured by stainless link chain.

SWIVEL ADAPTOR DOUBLE FEMALE ND265

In heat-treated light alloy, with stainless steel ball race for long wearing life. For connecting male fire hose coupling to inlets of breechings, hydroblenders, nozzles or pumps. Inlet and Outlet 38mm female BSP (Ref 026500). Or to client specs.



THREAD PROTECTOR ND11

In heat-treated light alloy for fine, clean and strong threads. Used to prevent damage to threaded bodies of pumps, breechings, hydroblenders, in fact any suitably threaded fire equipment. Inlet 38mm female thread, outlet 38mm male thread.

If you do not see what you want in our brochures, please call us! We cannot show every item
Due to continued improvement the right is reserved to modify specifications without prior notice



PSL

PO Box 69-028, 10 Akatea Road, Glendene, Auckland 0645, New Zealand
Ph: +64 9 8188048 Fax: +64 9 818 4484 Email: sales@firemaster.co.nz
Web: www.firemaster.co.nz

"Fire & Safety Solutions"

Rev: 2